



# ARIS Pacific Private Limited

Model		BTM-760Y	BTM-950Y	BTM-1100Y
Flat Patching section	Paper specification 1st (W×L)	760×760mm-100×150mm	950×760mm-100×150mm	1100×760mm-150×180mm
	Machine speed 1st (W×L)	Up to 12,000 sheets/hr 0~760mm	Up to 12,000 sheets/hr 0~760mm	Up to 10,000 sheets/hr 0~760mm
	Paper specification 2st (W×L)	760×420mm-100×150mm	950×420mm-100×150mm	1100×420mm-150×180mm
	Machine speed 2st (W×L)	Up to 24,000 sheets/hr 0~420mm	Up to 24,000 sheets/hr 0~420mm	Up to 20,000 sheets/hr 0~420mm
	Paper specification 3st (W×L)	760×260mm-100×150mm	950×260mm-100×150mm	1100×260mm-150×180mm
	Machine speed 3st (W×L)	Up to 36,000 sheets/hr 0~260mm	Up to 36,000 sheets/hr 0~260mm	Up to 30,000 sheets/hr 0~260mm
	Window dimension (W×L)	500×450mm-30×50mm	500×450mm-30×50mm	500×450mm-50×50mm
	Positioning accuracy	±1mm	±1mm	±1mm
Registration section	Paper specification 1st (W×L)	760×760mm-100×150mm	950×450mm-100×150mm	1100×760mm-150×180mm
	Machine speed 1st (W×L)	Up to 15,000 sheets/hr 0~760mm	Up to 15,000 sheets/hr 0~760mm	Up to 15,000 sheets/hr 0~760mm
	Paper specification 2st (W×L)	760×420mm-100×150mm	950×420mm-100×150mm	1100×420mm-150×180mm
	Machine speed 2st (W×L)	Up to 15,000 sheets/hr 0~420mm	Up to 15,000 sheets/hr 0~420mm	Up to 15,000 sheets/hr 0~420mm
	Window dimension (W×L)	500×400mm-30×50mm	500×400mm-30×50mm	500×400mm-50×50mm
	Positioning accuracy	±0.5mm	±0.5mm	±0.5mm
Paper weight/sheet thickness		Cardboard: 200–2000g/m <sup>2</sup> Corrugated board: 1–4mm		
Film thickness		PET: 0.03–0.2 PVC: 0.03–0.25		



## ARIS Pacific Private Limited

Model	BTM-760Y	BTM-950Y	BTM-1100Y
Power voltage	380V/50Hz		
Machine power	28kW		
Machine weight	3200kg	3500kg	4200kg
Overall dimension (L×W×H)	5500×1600×2080mm	5500×1850×2080mm	5500×2000×2080mm